

Datasheet for: 105504


Corner safety valve, G 1 1/4, Trigger pressure 3 bar

Corner safety valve, for saturated steam, Red brass, Operating temp. -10 to 185 °C, G 1 1/4, AF 50, Trigger pressure 3 bar . Type-tested, TÜV - SV. 749 D/G

Type number 222.06-3,0

Article number 105504

EAN/barcode



4047322040259

Your price 162,97 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	20.0 bar
Adjustment range min.	0.2 bar
Diaphragms	PTFE
H	152.0 mm
Housing	Bronze
Inlet and outlet	Open
Internal parts	Brass
L1	40.0 mm
L2	35.0 mm
Max. operating temperature	185 °C
Min. operating temperature	-10 °C
Min. set pressure	3.0 bar
Page No.	HK366
Page No. SF	SF059
Spring	C steel
Spring bonnet	Brass
Thread	G 1 1/4
a/f	50 mm

Variants

<i>Article number</i>	<i>Min. set pressure</i>	<i>Max. operating temperature</i>	<i>Diaphragms</i>	<i>Price</i>
105504	3.0 bar	185 °C	PTFE	162,97 € / Stk
105500	1.0 bar	135 °C	EPDM	162,97 € / Stk
105501	1.5 bar	135 °C	EPDM	162,97 € / Stk
105502	2.0 bar	135 °C	EPDM	162,97 € / Stk
105503	2.5 bar	135 °C	EPDM	162,97 € / Stk
105506	4.0 bar	150 °C	EPDM	162,97 € / Stk
105499	0.5 bar	135 °C	EPDM	162,97 € / Stk
105505	3.5 bar	150 °C	EPDM	162,97 € / Stk
105507	6.0 bar	150 °C	EPDM	162,97 € / Stk

More Pictures

