

Datasheet for: 105505


Corner safety valve, G 1 1/4, Trigger pressure 3.5 bar

Corner safety valve, for saturated steam, Red brass, Operating temp. -10 to 185 °C, G 1 1/4, AF 50, Trigger pressure 3.5 bar . Type-tested, TÜV – SV. 749 D/G

Type number	222.06-3,5
-------------	------------

Article number	105505
----------------	--------

EAN/barcode	 4047322248341
-------------	--

Your price	162,97 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	20.0 bar
Adjustment range min.	0.2 bar
Diaphragms	EPDM
H	152.0 mm
Housing	Bronze
Inlet and outlet	Open
Internal parts	Brass
L1	40.0 mm
L2	35.0 mm
Max. operating temperature	150 °C
Min. operating temperature	-10 °C
Min. set pressure	3.5 bar
Page No.	HK366
Page No. SF	SF059
Spring	C steel
Spring bonnet	Brass
Thread	G 1 1/4
a/f	50 mm

Variants

<i>Article number</i>	<i>Min. set pressure</i>	<i>Max. operating temperature</i>	<i>Diaphragms</i>	<i>Price</i>
105505	3.5 bar	150 °C	EPDM	162,97 € / Stk
105500	1.0 bar	135 °C	EPDM	162,97 € / Stk
105501	1.5 bar	135 °C	EPDM	162,97 € / Stk
105502	2.0 bar	135 °C	EPDM	162,97 € / Stk
105503	2.5 bar	135 °C	EPDM	162,97 € / Stk
105504	3.0 bar	185 °C	PTFE	162,97 € / Stk
105506	4.0 bar	150 °C	EPDM	162,97 € / Stk
105499	0.5 bar	135 °C	EPDM	162,97 € / Stk
105507	6.0 bar	150 °C	EPDM	162,97 € / Stk

More Pictures

