


Datasheet for: 133149


**Active charcoal filter »multifix«, PC container, Size 4, G 3/4**

Active charcoal filter »multifix« with PC container and protective cage, 0.005 mg/m<sup>3</sup>, Size 4, G 3/4, Input pressure max. 16 bar . For filtering odours out of compressed air. The activated carbon absorbs the oil vapour molecules contained in the compressed air. A separate filter route prevents activated carbon particles from entering the air flow.

Type number	FA 44 S
Article number	133149
EAN/barcode	 4047322476386
Your price	205,85 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	85.0 mm
B	241.0 mm
Bowl	Polycarbonate container with protective cage
C	58.0 mm
D	183.0 mm
DN	20.0
Filter element	Activated carbon-POM
Flow rate	3000 l/min
Flow rate measurement	At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar
Housing	Die-cast aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK088
Residual oil content	0.005 mg/m <sup>3</sup>
Sealant	NBR
Series	multifix
Size	4
Thread	G 3/4

## Variants

Article number	Thread	Housing	Flow rate	Size	DN	Price
133149	G 3/4	Die-cast aluminium	3000 l/min	4	20.0	205,85 € / Stk
100541	G 1/4	Die-cast zinc	380 l/min	1	6.0	96,11 € / Stk
100542	G 1/2	Die-cast zinc	1500 l/min	3	15.0	152,24 € / Stk
133150	G 1	Die-cast aluminium	3000 l/min	4	25.0	205,85 € / Stk

## More Pictures

