

Datasheet for: 101643



Proportional control valve »posiflow«, 24 V DC, NC, G 3/8, DN 5.6

Proportional control valve »posiflow«, for air / gas, 24 V DC, NC, G 3/8, DN 5.6, Operating pressure difference max. 1.4 bar . For electronic flow control. For all applications where the flow rate of a liquid or gas has to be controlled. The valve features a special magnet armature and is characterised by low friction and a high dynamic response. If the valve is combined with a plug amplifier: The maximum / minimum current and frequency can be adjusted by means of integrated potentiometers. A current ramp can also be connected and adjusted with a potentiometer. This facilitates a slow change in the flow rate, even if the setpoint changes suddenly. If the setpoint is < 200 mV (< 0.4 / 4.4 mA), the piloting current is completely switched off, causing the valve to be de-energised (tightly closed function). We recommend combining these proportional valves with a plug amplifier. Benefits: - Compact and economical - Integrated temperature compensation - Precise control - Optimised flow with no water hammer - Ramp function assures a smooth response to step changes in the input signal - Disconnect function

Type number	PV 2015
Article number	101643
EAN/barcode	4047322163446
Your price	206,95 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A B C DN Failsafe beha- viour Housing Internal parts Max. ambient temperature Max. medium	85.0 mm 48.0 mm 97.0 mm 5.6 Tight closure in case of loss of voltage Brass Stainless steel 75 °C
temperature	90 °C

Created on: 18. Juni 2020 User: 18. Juni 2020 Gast

Page: 1 / 2



Max. operating pressure difference Medium

Min. ambient

temperature Min. medium temperature Page No. Piloting Pressure range

Sealant Thread Valve disc Valve seat 1.4 bar

Air, neutral gases, water, oil

-10 °C

-10 °C

HK186


Via plug amplifier to 10 V, to 20 mA, 4 to 20 mA Vacuum to 8 bar


FKM G 3/8 FKM **Brass**

Variants

Article number	Q _e		Max, Operating Dressure difference	
Artic	Desury.	70	N to	i. Q
101643	G 3/8	5.6	1.4 bar	206,95 € / Stk
101641	G 1/4	2.4	8.0 bar	184,24 € / Stk
101642	G 1/4	3.2	4.0 bar	184,24 € / Stk
101644	G 3/8	7.1	1.0 bar	206,95 € / Stk

More Pictures





RIEGLER & Co. KG Schützenstraße 27 72574 Bad Urach DE

Contact: +49 7125 9497-8320 +49 7125 9497-95 shop@riegler.de

Created on: 18. Juni 2020 User: Gast

Page: 2/2