

Datasheet for: 105612


Corner safety valve, liquids, G 1 1/4, Trigger pressure 2.5 bar

Corner safety valve, for liquids, Red brass, Operating temp. -10 °C to 110 °C, G 1 1/4, AF 50, Trigger pressure 2.5 bar . For non-toxic, non-flammable liquids. No evaporation allowed when blowing off. With diaphragm to protect the spring and with lifting device. Type-tested, TÜV-SV. 749. F

Type number	221.06-2,5
-------------	------------

Article number	105612
----------------	--------

EAN/barcode	
-------------	--



4047322218726

Your price	163,20 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	16.0 bar
Adjustment range min.	1.0 bar
Diaphragms	NBR
H	152.0 mm
Housing	Bronze
Inlet and outlet	Each with female thread acc. to DIN EN ISO 228-1
Internal parts	Brass
L1	40.0 mm
L2	35.0 mm
Max. operating temperature	110 °C
Min. operating temperature	-10 °C
Min. set pressure	2.5 bar
Page No.	HK367
Page No. SF	SF060
Spring	C steel
Spring bonnet	Brass
Thread	G 1 1/4
a/f	50 mm

Variants

Article number	Min. set pressure	Price
105612	2.5 bar	163,20 € / Stk
105611	2.0 bar	163,20 € / Stk
105613	3.0 bar	163,20 € / Stk
105615	4.0 bar	163,20 € / Stk
105617	5.0 bar	163,20 € / Stk
105619	6.0 bar	163,20 € / Stk
105621	7.0 bar	163,20 € / Stk
105609	1.0 bar	163,20 € / Stk
105623	10.0 bar	163,20 € / Stk
105622	8.0 bar	163,20 € / Stk
105610	1.5 bar	163,20 € / Stk
105624	11.0 bar	163,20 € / Stk
105614	3.5 bar	163,20 € / Stk
105618	5.4 bar	163,20 € / Stk
105620	6.6 bar	111,95 € / Stk
105616	4.2 bar	163,20 € / Stk
125303	4.5 bar	163,20 € / Stk

More Pictures

