


## Datasheet for: 101097


**Combi-service unit with PC container, Size 2, G 1, 0.5 - 16 bar**

Combi-service unit with PC container and manual bleeder valve, Size 2, G 1, Input pressure max. 16 bar, Control range 0.5 - 16 bar . A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design. The pressure setting can be locked by pushing the knob down. Oil can be filled under pressure.

Type number	811.16 K
Article number	101097
EAN/barcode	 4047322120074
Your price	209,57 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	93.0 mm
B	296.5 mm
Bowl	Polycarbonate container
C	96.5 mm
Condensate drain	Manual drain valve
Filter rating	50.0 $\mu\text{m}$
Flow rate	2800 l/min
Flow rate measurement	At $P_1 = 8 \text{ bar}$ , $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. control range	16.0 bar
Max. input pressure	16 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	HK134
Sealant	NBR
Sight dome	PA
Size	2

Spring bonnet  
 Thread

 PA  
 G 1

## Variants

Article number	Thread	Max. control range	Flow rate	Size	Price
101097	G 1	16.0 bar	2800 l/min	2	209,57 € / Stk
101088	G 1/4	10.0 bar	1400 l/min	1	128,83 € / Stk
101089	G 1/4	16.0 bar	1000 l/min	1	128,83 € / Stk
101090	G 3/8	10.0 bar	1400 l/min	1	128,60 € / Stk
101091	G 3/8	16.0 bar	1000 l/min	1	128,60 € / Stk
101092	G 1/2	10.0 bar	1400 l/min	1	127,54 € / Stk
101093	G 1/2	16.0 bar	1000 l/min	1	127,54 € / Stk
101094	G 3/4	10.0 bar	3400 l/min	2	212,24 € / Stk
101095	G 3/4	16.0 bar	2800 l/min	2	212,24 € / Stk
101096	G 1	10.0 bar	3400 l/min	2	209,57 € / Stk

## More Pictures

