


## Datasheet for: 156610


**3/2-way valve »FUTURA«, electr. actuated, 24 V AC, Size 4, G 3/4**

3/2-way valve »FUTURA«, electr. actuated with solenoid 24 V AC, 50 Hz, Size 4, G 3/4, Exhaust G 1/2, Input pressure 2 - 10 bar . Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. 3/2-way type including silencer. When they are switched off, the system is exhausted at the same time.

Type number	FU 975-AC
Article number	156610
EAN/barcode	 4047322628013
Your price	210,98 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	85.0 mm
B	177.7 mm
C	110.7 mm
Connecting thread	Material: Die-cast zinc
Duty cycle	100 %
Electrical connection	Socket coupling EN 175301-803, form C, poles 2+PE
Exhaust air	G 1/2
Flow rate	12500 l/min
Flow rate measurement	At P <sub>2</sub> = 6 bar and pressure drop $\Delta_p$ = 1 bar
Holding power with 50 Hz AC voltage	1.6 VA
Housing	PA66 GF60
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.0 bar
Min. temperature range	-10 °C
Page No.	HK055

Pick-up power with 50 Hz AC voltage	2.2 VA
Power input	2.5 Watt with DC voltage
Protection IP	IP 65
Series	FUTURA
Size	4
Thread	G 3/4

## Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
156610	G 3/4	G 1/2	12500 l/min	4	210,98 € / Stk
156606	G 1/4	G 1/4	2000 l/min	1	95,39 € / Stk
156611	G 1	G 1/2	12500 l/min	4	210,98 € / Stk
156608	G 3/8	G 1/2	4500 l/min	2	101,62 € / Stk
156607	G 3/8	G 1/4	2000 l/min	1	95,39 € / Stk
156609	G 1/2	G 1/2	4500 l/min	2	101,62 € / Stk

## More Pictures

