


Datasheet for: 101020



Mist oiler »Standard«, Polycarbonate container, Size 4, G 1 1/4

Mist oiler »Standard« with polycarbonate container, Size 4, G 1 1/4, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C . Proportional lubricators, oil can be filled under pressure.

Type number	763 K
Article number	101020
EAN/barcode	 4047322117708
Your price	211,30 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	137.0 mm
Bowl	Polycarbonate container
C	70.0 mm
D	232.0 mm
DN	40.0
Flow rate	9000 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK128
Sealant	NBR
Series	Standard
Sight dome	PA
Size	4
Thread	G 1 1/4

Variants

Article number	Thread	Flow rate	Size	DN	Price
101020	G 1 1/4	9000 l/min	4	40.0	211,30 € / Stk
101014	G 1/4	1200 l/min	1	6.0	35,04 € / Stk
101015	G 3/8	1200 l/min	1	6.0	35,04 € / Stk
101016	G 3/8	2400 l/min	2	10.0	51,34 € / Stk
101017	G 1/2	4000 l/min	3	15.0	56,28 € / Stk
101018	G 3/4	9000 l/min	3	20.0	99,13 € / Stk
101019	G 1	9000 l/min	3	25.0	98,16 € / Stk
101021	G 1 1/2	9000 l/min	4	45.0	209,25 € / Stk

More Pictures

