


Datasheet for: 101083


Service unit 3-part »Standard«, Metal container, Size 3, G 1/2

Service unit 3-part »Standard«, Metal container, metal drip cap, Size 3, G 1/2, Input press. max. 25 bar, Control range 0.5-16 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	850 C/M
Article number	101083
EAN/barcode	 4047322121415
Your price	211,92 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	259.0 mm
B	226.0 mm
Bowl	Metal container
C	55.0 mm
Condensate drain	Manuel
DN	15.0
Filter rating	5.0 μ m
Flow rate	3200 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	16.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK132
Pressure gauge display max.	25.0 bar
Pressure gauge display min.	0.0 bar
Pressure gauge \emptyset	63 mm

Sealant
 Series
 Sight dome
 Size
 Thread

NBR
 Standard
 Zinc-glass-NBR
 3
 G 1/2

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
101083	G 1/2	5.0 μm	3200 l/min	3	15.0	211,92 € / Stk
101080	G 1/4	5.0 μm	600 l/min	1	6.0	141,88 € / Stk
101081	G 3/8	5.0 μm	600 l/min	1	6.0	141,88 € / Stk
101082	G 3/8	40.0 μm	1400 l/min	2	6.0	195,35 € / Stk
101084	G 3/4	5.0 μm	3200 l/min	3	20.0	388,71 € / Stk
101085	G 1	5.0 μm	3200 l/min	3	25.0	388,71 € / Stk
101086	G 1 1/4	40.0 μm	5000 l/min	4	25.0	782,55 € / Stk
101087	G 1 1/2	40.0 μm	5000 l/min	4	35.0	745,06 € / Stk

More Pictures

