


## Datasheet for: 159745


**3-way brass ball valve, Pneumat. actuation drive, T-hole, Rp 1**

3-way brass ball valve, Pneumat. actuation drive, T-hole, Operating temperature -20 °C to 70 °C, Rp 1, DN 25, PN max. 40 bar . 3-way cock, L-bore or T-bore, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Type number	KHRP1MSANTDT3
Article number	159745
EAN/barcode	 4047322643719
Your price	425,00 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	133.0 mm
Angle of rotation	90 °
B	150.5 mm
D	30.0 mm
DN	25.0
L	97.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
PN	40 bar
Page No.	HK300
Position	T 3
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1
Valve adapter	Supplied as standard
Version	double-acting
a/f	41 mm

## Variants

Article number	Thread	DN	PN	a/f	Price
159745	Rp 1	25.0	40 bar	41 mm	425,00 € / Stk
103559	Rp 3/4	20.0	40 bar	31 mm	314,63 € / Stk
103561	Rp 1 1/4	32.0	40 bar	55 mm	438,10 € / Stk
103562	Rp 1 1/2	40.0	25 bar	55 mm	735,27 € / Stk
103563	Rp 2	50.0	25 bar	67 mm	982,23 € / Stk
159744	Rp 1/2	15.0	40 bar	25 mm	244,08 € / Stk

## More Pictures

