

Stainless steel V4A

High-quality series in V4A stainless steel. For quick and simple hose connections.
 User friendly; the coupling elements are joined without damaging the seal.
 Applications: Industrial plant engineering, shipbuilding, chemical industry

Material	Stainless steel V4A
Sealant	FKM
Operating pressure	max. 16 bar
Operating temperature	-15 °C to +200 °C

Storz couplings with hose stem, swivel type, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance mm	Hose I.D. mm	Length mm	Weight (kg)
3401.3119	108283	25-D	31.0	19	58.0	0.3
3401.3125	108284	25-D	31.0	25	54.0	0.3
3401.5138	108285	38	51.0	38	90.0	0.7
3401.6625	108286	52-C	66.0	25	88.0	1.0
3401.6632	108287	52-C	66.0	32	88.0	1.0
3401.6638	108288	52-C	66.0	38	90.0	1.0
3401.6642	108289	52-C	66.0	42	90.0	1.0
3401.6652	108290	52-C	66.0	52	90.0	1.0
3401.8138	108291	65	81.0	38	90.0	1.4
3401.8152	108292	65	81.0	52	99.0	1.4
3401.8165	108293	65	81.0	65	99.0	1.4
3401.8175	108294	65	81.0	75	99.0	1.5
3401.8965	108295	75-B	89.0	65	124.0	1.7
3401.8975	108296	75-B	89.0	75	124.0	1.8
3401.115100	108297	100	115.0	100	152.0	3.8
3401.133100	108298	110-A	133.0	100	167.0	4.6



3401.6625

Storz couplings with hose stem for safety clamp, swivel type, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance mm	Hose I.D. mm	Length mm	Weight (kg)
3402.3119	108299	25-D	31.0	19	74.0	0.3
3402.3125	108300	25-D	31.0	25	74.0	0.3
3402.6638	108301	52-C	66.0	38	90.0	1.1
3402.6650	108302	52-C	66.0	50	95.0	1.0
3402.8975	108303	75-B	89.0	75	114.0	2.3
3402.133100	108304	110-A	133.0	100	157.0	4.5



3402.6650

Storz fixed couplings, male threaded, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance mm	Female thread	Weight (kg)
3403.3134	108305	25-D	31.0	G 3/4	0.2
3403.3110	108306	25-D	31.0	G 1	0.2
3403.4410	108307	32	44.0	G 1	0.4
3403.44114	108308	32	44.0	G 1 1/4	0.4
3403.51114	108309	38	51.0	G 1 1/4	0.6
3403.51112	108310	38	51.0	G 1 1/2	0.5
3403.6610	108311	52-C	66.0	G 1	0.7
3403.66114	108312	52-C	66.0	G 1 1/4	0.7
3403.66112	108313	52-C	66.0	G 1 1/2	0.7
3403.6620	108314	52-C	66.0	G 2	0.7
3403.8120	108315	65	81.0	G 2	1.0
3403.81212	108316	65	81.0	G 2 1/2	1.1
3403.89212	108317	75-B	89.0	G 2 1/2	1.1
3403.8930	108318	75-B	89.0	G 3	1.3
3403.11540	108319	100	115.0	G 4	2.8
3403.13340	108320	100-A	133.0	G 4	3.0



3403.66114

Storz fixed couplings, female threaded, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance mm	Female thread
3404.3112	108321	25-D	31.0	G 1/2
3404.3134	108322	25-D	31.0	G 3/4
3404.3110	108323	25-D	31.0	G 1
3404.4410	108324	32	44.0	G 1
3404.44114	108325	32	44.0	G 1 1/4
3404.51114	108326	38	51.0	G 1 1/4
3404.51112	108327	38	51.0	G 1 1/2
3404.6610	108328	52-C	66.0	G 1
3404.66114	108329	52-C	66.0	G 1 1/4
3404.66112	108330	52-C	66.0	G 1 1/2
3404.6620	108331	52-C	66.0	G 2
3404.66212	108332	52-C	66.0	G 2 1/2
3404.8120	108333	65	81.0	G 2
3404.81212	108334	65	81.0	G 2 1/2
3404.8130	108335	65	81.0	G 3
3404.8920	108336	75-B	89.0	G 2
3404.89212	108337	75-B	89.0	G 2 1/2
3404.8930	108338	75-B	89.0	G 3
3404.11540	108339	100	115.0	G 4
3404.13340	108340	100-A	133.0	G 4



3404.66112

Storz adapters, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance 1 mm	Lug distance 2 mm	Weight (kg)
3405.6631	108341	52-C/25-D	66.0	31.0	1.3
3405.8166	108342	65/52-C	81.0	66.0	2.0
3405.8966	108343	75-B/52-C	89.0	66.0	2.2
3405.8981	108344	75-B/65	89.0	81.0	2.1
3405.11589	108345	100/75-B	115.0	89.0	3.8
3405.13389	108346	110-A/75-B	133.0	89.0	4.5
3405.133115	108347	110-A/100	133.0	115.0	5.2



3405.6631

Storz adapters to flange, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance mm	Flange	Hole circle Ø mm	No. of bolt holes	Weight (kg)
3406.3125	108348	25-D	31,0	DN 25	85.0	4	1.4
3406.6650	108349	52-C	66,0	DN 50	125.0	4	3.3
3406.8165	108350	65	81,0	DN 65	145.0	4	3.9
3406.8965	108351	75-B	89,0	DN 65	145.0	4	4.4
3406.8980	108352	75-B	89,0	DN 80	160.0	8	5.6
3406.115100	108353	100	115,0	DN 100	180.0	8	6.8
3406.133100	108354	100-A	133,0	DN 100	180.0	8	8.1



3406.6650



3406.8980

Storz blank caps with chain, stainless steel

Art. No.	Ident No.	Storz-size	Lug distance mm	Weight (kg)
3407.31	108355	25-D	31.0	0.3
3407.44	108356	32	44.0	0.4
3407.51	108357	38	51.0	0.5
3407.66	108358	52-C	66.0	0.9
3407.81	108359	65	81.0	1.3
3407.89	108360	75-B	89.0	1.3
3407.115	108361	100	115.0	2.7
3407.133	108362	100-A	133.0	3.7



3407.66

Jet / spray branch pipes acc. to DIN 14365, aluminium

Art. No.	Ident No.	Material	Thread	Nozzel	Storz-size	Weight (kg)
2408.100	108267	Handle and nozzle: plastic	G 1 male	4.0 mm	25-D	0.4
2408.200	108268	Handle and nozzle: plastic	G 2 male	9.0 mm	52-C	0.9
2408.300	108269	Rubberised handle	G 2 male	9.0 mm	52-C	1.3
2408.400	108270	Rubberised handle with additional water curtain	G 2 male	9.0 mm	52-C	1.5
2408.500	108271	Rubberised handle with additional water curtain	G 2 1/2 male	16.0 mm	75-B	2.0



2408.100



2408.300



2408.400

Spanner for Storz couplings

Art. No.	Ident No.	For lug distance	Material	Weight (kg)
2408.600	108272	31.0	Steel	0.2
2408.700	108273	66.0 ; 89.0 ; 133.0	Malleable iron	0.8



2408.600



2408.700

Replacement seals for Storz couplings, FKM

Art. No.	Ident No.	Storz-size	Lug distance mm
3408.31	108363	25-D	31.0
3408.44	108364	32	44.0
3408.66	108365	52-C	66.0
3408.81	108366	65	81.0
3408.89	108367	75-B	89.0
3408.115	108368	100	115.0
3408.133	108369	110-A	133.0
3408.51	108370	38	51.0



3408.51