

Datasheet for: 103621


Stainless steel ball valve, Pneumat. actuation drive, L-hole

3-way stainless steel ball valve, Pneumat. actuation drive, L-hole, Operating temp. -20°C to 70°C, Rp 3/4, DN 20, PN max. 63 bar . 3-way cock, reduced bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback. Standardised interfaces: Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211. Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845. Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Type number	350.633-L1
Article number	103621
EAN/barcode	 4047322076968
Your price	455,47 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	137.0 mm
Angle of rotation	90 °
B	159.0 mm
D	23.0 mm
DN	20.0
L	80.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401, with ISO flange plate
Max. operating pressure	63 bar
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
Page No.	HK303
Position	L 2
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM

Thread
 Valve adapter
 Version
 a/f

Rp 3/4
 Acc. to NAMUR
 single-acting
 32 mm

Variants

Article number	Thread	DN	a/f	Price
103621	Rp 3/4	20.0	32 mm	455,47 € / Stk
103620	Rp 1/2	15.0	27 mm	390,59 € / Stk
103622	Rp 1	25.0	41 mm	567,76 € / Stk
103623	Rp 1 1/4	32.0	50 mm	742,37 € / Stk
103624	Rp 1 1/2	40.0	55 mm	847,23 € / Stk
103625	Rp 2	50.0	71 mm	1.126,44 € / Stk

More Pictures

