

Datasheet for: 101192


Stainless steel pressure regulator, 1.4404, G 1/4, 1 - 15 bar

Stainless steel pressure regulator, 1.4404, with secondary venting (reversible), G 1/4, Control range 1 - 15 bar .
 Stainless steel regulators containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Type number	570.14 D
-------------	----------

Article number	101192
----------------	--------

EAN/barcode	 4047322101806
-------------	--

Your price	458,15 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	65.0 mm
B	162.0 mm
C	37.0 mm
D	125.0 mm
Diaphragms	PTFE
Flow rate	330 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p \leq 1$ bar
Housing	Stainless steel 1.4404 (AISI 316L)
Max. ambient temperature	80 °C
Max. control range	15.0 bar
Max. input pressure	50 bar
Max. medium temperature	80 °C
Min. control range	1.0 bar
Page No.	HK146
Sealant	FKM
Thread	G 1/4

Variants

Article number	Thread	Max. input pressure	Min. control range	Max. control range	Flow rate	Price
101192	G 1/4	50 bar	1.0 bar	15.0 bar	330 l/min	458,15 € / Stk
101191	G 1/4	30 bar	0.5 bar	8.0 bar	200 l/min	458,15 € / Stk
101193	G 1/2	30 bar	0.5 bar	8.0 bar	660 l/min	693,32 € / Stk
101194	G 1/2	50 bar	1.0 bar	15.0 bar	1800 l/min	693,32 € / Stk

More Pictures

