


Datasheet for: 103556


3-way brass ball valve, Pneumat. actuation drive, L-hole, Rp 1

3-way brass ball valve, Pneumat. actuation drive, L-hole, Operating temperature -20 °C to 70 °C, Rp 1, DN 25, PN max. 40 bar . 3-way cock, L-bore or T-bore, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Type number	350.712
Article number	103556
EAN/barcode	 4047322077064
Your price	459,31 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	133.0 mm
Angle of rotation	90 °
B	150.5 mm
D	30.0 mm
DN	25.0
L	97.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
PN	40 bar
Page No.	HK300
Position	L 2
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1
Valve adapter	Supplied as standard
Version	single-acting
a/f	41 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103556	Rp 1	25.0	40 bar	41 mm	459,31 € / Stk
103555	Rp 1/2	15.0	40 bar	25 mm	295,87 € / Stk
103557	Rp 1 1/2	40.0	25 bar	55 mm	642,07 € / Stk

More Pictures

