

## Datasheet for: 139512



**Active charcoal filter »FUTURA«, Metal container, Size 2, G 3/8**

Active charcoal filter »FUTURA« with metal container and viewing tube, 0.005 mg/m<sup>3</sup>, Size 2, G 3/8, Input pressure - 16 bar . Activated carbon filters in modern design for compliance with strict compressed air purity requirements. Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m<sup>3</sup> from compressed air and gases.

Type number	FU 893-M
-------------	----------

Article number	139512
----------------	--------

EAN/barcode	
-------------	--



4047322534420

Your price	163,68 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	63.0 mm
B	187.5 mm
Bowl	Metal container with viewing tube
C	42.5 mm
Connecting thread	Material: Die-cast zinc
Filter element	Activated carbon
Flow rate	1700 l/min
Flow rate measurement	At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	0.0 bar
Min. temperature range	-10 °C
Page No.	HK041
Residual oil content	0.005 mg/m <sup>3</sup>
Series	FUTURA
Size	2
Thread	G 3/8

## Variants

Article number	Thread	Flow rate	Size	Price
139512	G 3/8	1700 l/min	2	163,68 € / Stk
139513	G 1/2	1700 l/min	2	163,68 € / Stk
156647	G 3/8	470 l/min	1	98,16 € / Stk
156646	G 1/4	470 l/min	1	98,16 € / Stk
156649	G 1	2500 l/min	4	203,37 € / Stk
156648	G 3/4	2500 l/min	4	203,37 € / Stk

## More Pictures

