


Datasheet for: 133144


Start up valve »multifix«, with adjustable throttle, Size 4, G 1

Start up valve »multifix«, with adjustable throttle, Size 4, G 1, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C . Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

Type number	A 45 F
Article number	133144
EAN/barcode	 4047322476331
Your price	165,02 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	85.0 mm
B	119.0 mm
D	53.0 mm
Flow rate	10000 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. input pressure	2.0 bar
Page No.	HK099
Sealant	NBR
Series	multifix
Size	4
Thread	G 1

Variants

Article number	Thread	Housing	Flow rate	Size	Price
133144	G 1	Die-cast aluminium	10000 l/min	4	165,02 € / Stk
100626	G 1/4	Die-cast zinc	1000 l/min	1	52,04 € / Stk
100627	G 1/2	Die-cast zinc	4000 l/min	3	55,72 € / Stk
100629	G 1	Aluminium	12000 l/min	5	196,07 € / Stk
100628	G 3/4	Aluminium	12000 l/min	5	196,07 € / Stk
133143	G 3/4	Die-cast aluminium	10000 l/min	4	165,02 € / Stk

More Pictures

