


## Datasheet for: 101067


**Service unit 3-part »Standard« with PC container, Size 3, G 1/2**

Service unit 3-part »Standard« with polycarbonate container, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.5 - 10 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	850 C
Article number	101067
EAN/barcode	 4047322121392
Your price	165,20 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	259.0 mm
B	223.4 mm
Bowl	Polycarbonate container
C	55.0 mm
Condensate drain	Semi-automatic
DN	15.0
Filter rating	5.0 $\mu$ m
Flow rate	3200 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK132
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar

Pressure gauge	63 mm
Ø	
Sealant	NBR
Series	Standard
Sight dome	PA
Size	3
Thread	G 1/2

## Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
101067	G 1/2	5.0 µm	3200 l/min	3	15.0	165,20 € / Stk
101064	G 1/4	5.0 µm	600 l/min	1	6.0	100,37 € / Stk
101065	G 3/8	5.0 µm	600 l/min	1	6.0	100,37 € / Stk
101066	G 3/8	40.0 µm	1400 l/min	2	6.0	146,51 € / Stk
101068	G 3/4	5.0 µm	3200 l/min	3	20.0	340,11 € / Stk
101069	G 1	5.0 µm	3200 l/min	3	25.0	340,76 € / Stk
101070	G 1 1/4	40.0 µm	5000 l/min	4	25.0	737,48 € / Stk
101071	G 1 1/2	40.0 µm	5000 l/min	4	35.0	694,68 € / Stk

## More Pictures

