

Datasheet for: 103609


Stainless steel ball valve, Pneumat. actuation drive, Rp 1 1/4

2-way stainless steel ball valve, Pneumat. actuation drive, single-acting, Operating temp. -20°C to 70°C, Rp 1 1/4, PN max 63 bar . 2-way cock, 3-piece, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback. Standardised interfaces:
 Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211. Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.
 Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Type number	350.523
Article number	103609
EAN/barcode	 4047322076616
Your price	466,40 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	161.0 mm
Angle of rotation	90 °
B	188.0 mm
D	37.0 mm
DN	32.0
L	110.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401, with ISO flange plate
Max. operating pressure	63 bar
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
Page No.	HK302
Sealant actuator	NBR
Sealant ball valve	PTFE
Thread	Rp 1 1/4

Valve adapter
 Version
 a/f

Acc. to NAMUR
 single-acting - spring to close
 50 mm

Variants

Article number	Thread	DN	a/f	Price
103609	Rp 1 1/4	32.0	50 mm	466,40 € / Stk
103605	Rp 1/2	15.0	29 mm	307,30 € / Stk
103606	Rp 1/2	15.0	29 mm	265,12 € / Stk
103607	Rp 3/4	20.0	35 mm	370,89 € / Stk
103608	Rp 1	25.0	41 mm	424,36 € / Stk
103610	Rp 1 1/2	40.0	58 mm	639,53 € / Stk
103611	Rp 2	50.0	74 mm	728,16 € / Stk
103612	Rp 2 1/2	65.0	85 mm	1.135,76 € / Stk
103613	Rp 3	80.0	100 mm	1.496,63 € / Stk

More Pictures

