

Datasheet for: 106519


5/3-way valve pneumatic monostable G 1/2 mid-position pressurised

5/3-way valve pneumatic, monost. G 1/2, mid-position pressurised, Operating pre. 2.5 to 10 bar, Operating temp. -10°C to 60°C .

Type number	516.603
Article number	106519
EAN/barcode	 4047322097338
Your price	166,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/2
DN	15.0
Flow rate 1	3200 NI/min
Flow rate 2	4600 NI/min
Flow rate measurement 1	Flow rate at 6 bar and Δp 0.5 bar
Flow rate measurement 2	Flow rate at 6 bar and Δp 1.0 bar
Function	5/3
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Mid-position pressurised
Page No.	HK466
Symbol	31

Variants

Article number	Connection	DN	Flow rate 1	Flow rate 2	Price
106519	G 1/2	15.0	3200 NI/min	4600 NI/min	166,07 € / Stk
106508	G 1/8	5.0	400 NI/min	550 NI/min	42,93 € / Stk
106509	G 1/8	5.0	400 NI/min	550 NI/min	42,93 € / Stk
106510	G 1/8	5.0	400 NI/min	550 NI/min	42,93 € / Stk
106511	G 1/4	7.5	750 NI/min	1100 NI/min	53,87 € / Stk
106512	G 1/4	7.5	750 NI/min	1100 NI/min	53,87 € / Stk
106513	G 1/4	7.5	750 NI/min	1100 NI/min	53,87 € / Stk
106517	G 1/2	15.0	3200 NI/min	4600 NI/min	166,07 € / Stk
106518	G 1/2	15.0	3200 NI/min	4600 NI/min	166,07 € / Stk
106515	G 3/8	13.3	1560 NI/min	2150 NI/min	94,38 € / Stk
106516	G 3/8	13.3	1560 NI/min	2150 NI/min	94,38 € / Stk
106514	G 3/8	13.3	1560 NI/min	2150 NI/min	94,38 € / Stk

More Pictures

