


## Datasheet for: 102859


**2/2-way solenoid valve, NC, pilot operated, 230 V, 50 - 60 Hz**

2/2-way solenoid valve brass, NC, pilot operated, 230 V, 50 - 60 Hz, Medium temperature -20 °C to 120 °C, Rp 3/4, PN 0.35 - 9 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1228
Article number	102859
EAN/barcode	 4047322158251
Your price	167,39 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	75.0 mm
B	71.0 mm
DN	19.0
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	50 °C
Max. medium temperature	120 °C
Max. operating pressure	9 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Min. operating pressure	0.35 bar
Page No.	HK319
Protection IP	IP65 (with connector socket fitted)
Sealant	FKM
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 3/4
Type	3

Valve seat

Brass

## Variants

Article number	Thread	Max. operating pressure	Max. medium temperature	DN	Sealant	Price
102859	Rp 3/4	9 bar	120 °C	19.0	FKM	167,39 € / Stk
102854	Rp 3/8	14 bar	85 °C	16.0	NBR	100,67 € / Stk
102855	Rp 3/8	14 bar	120 °C	16.0	FKM	114,47 € / Stk
102856	Rp 1/2	14 bar	85 °C	16.0	NBR	101,37 € / Stk
102857	Rp 1/2	14 bar	120 °C	16.0	FKM	114,47 € / Stk
102858	Rp 3/4	9 bar	85 °C	19.0	NBR	151,93 € / Stk
102860	Rp 1	9 bar	85 °C	25.0	NBR	204,38 € / Stk
102861	Rp 1	9 bar	120 °C	25.0	FKM	277,05 € / Stk
102862	Rp 1 1/4	9 bar	85 °C	28.0	NBR	254,36 € / Stk
102863	Rp 1 1/4	9 bar	120 °C	28.0	FKM	356,31 € / Stk
102864	Rp 1 1/2	9 bar	85 °C	32.0	NBR	312,41 € / Stk
102865	Rp 1 1/2	9 bar	120 °C	32.0	FKM	494,91 € / Stk
102866	Rp 2	9 bar	85 °C	44.0	NBR	486,24 € / Stk

## More Pictures

