


## Datasheet for: 135221


**Push-in T-fitting L-shape rotating G 3/8 o. for hose exterior Ø14**

Push-in T-fitting, L-shape, rotating, G 3/8 o., for hose exterior Ø 14 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	871.038-14 ES
Article number	135221
EAN/barcode	 4047322494267
Your price	168,02 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For tube O.D.	14 mm
L1	28.7 mm
L2	64.1 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK721
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 3/8
Working pressure pulsate a/f	10.0 bar 22 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
135221	G 3/8	14 mm	22 mm	168,02 € / Stk
135222	G 1/2	10 mm	27 mm	132,74 € / Stk
135214	G 1/4	6 mm	17 mm	69,17 € / Stk
135224	G 1/2	14 mm	27 mm	180,95 € / Stk
135209	M5	4 mm	11 mm	72,66 € / Stk
135218	G 3/8	8 mm	21 mm	95,36 € / Stk
135216	G 1/4	10 mm	17 mm	115,62 € / Stk
135219	G 3/8	10 mm	21 mm	124,00 € / Stk
135212	G 1/8	8 mm	14 mm	74,05 € / Stk
135225	G 1/2	16 mm	27 mm	197,01 € / Stk
135211	G 1/8	6 mm	14 mm	64,63 € / Stk
135215	G 1/4	8 mm	17 mm	78,60 € / Stk
135217	G 1/4	12 mm	19 mm	145,67 € / Stk
135210	G 1/8	4 mm	14 mm	62,18 € / Stk
135220	G 3/8	12 mm	21 mm	151,61 € / Stk
135213	G 1/4	4 mm	17 mm	67,07 € / Stk
135223	G 1/2	12 mm	27 mm	155,09 € / Stk

## More Pictures

