

Single-lever operation: Inflation, deflation and checking with a single handle.

These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value. With push-in plug for DN 7.2 coupling.

To check                    lever in home position  
 To deflate                 lever actuated half-way  
 To inflate                 lever fully actuated

Operating temperature                 -10 °C to +60 °C

Handheld tyre gauges with tyre valve connector				
Art. No.	Ident No.	Measuring range bar	Weight kg	
36.011	114514	0 to 4 bar / 56 psi	1.051	calibrated
36.012	114515	0 to 4 bar / 56 psi	1.025	uncalibrated
36.013	114516	0 to 12 bar / 170 psi	1.033	calibrated
36.014	114517	0 to 12 bar / 170 psi	1.046	uncalibrated
36.015	114518	0 to 25 bar / 350 psi	1.054	uncalibrated



36.013

Handheld tyre gauges with twin hold-on connector				
Art. No.	Ident No.	Measuring range bar	Weight kg	
37.012	-	0 to 4 bar / 56 psi	1.153	uncalibrated
37.013	114519	0 to 12 bar / 170 psi	1.151	calibrated
37.014	114520	0 to 12 bar / 170 psi	1.162	uncalibrated
37.015	114521	0 to 25 bar / 350 psi	1.110	uncalibrated



37.013

Handheld tyre gauges with clip-on connector				
Art. No.	Ident No.	Measuring range bar	Weight kg	
34.011	114522	0 to 4 bar / 56 psi	1.039	calibrated
34.012	114523	0 to 4 bar / 56 psi	1.042	uncalibrated
34.013	114524	0 to 12 bar / 170 psi	1.039	calibrated
34.014	114525	0 to 12 bar / 170 psi	1.079	uncalibrated



34.014

### Connector

Art. No.	Ident No.	Designation
36.030	114530	Tyre valve connector
36.020	114531	Clip-on connector
37.030	114532	Twin hold-on connector



36.030

### Replacement hoses

Art. No.	Ident No.	Designation
36.250	114534	Hose, complete with tyre valve connector for 36.011 - 36.015 gauges
37.250	114536	Hose, complete with twin hold-on connector for 37.011 - 37.015 gauges
38.250	114538	Hose, complete with clip-on connector for 34.011 to 34.014 gauges



36.250

### Pressure gauges

Art. No.	Ident No.	Designation
36.40	114540	Pressure gauge 0 to 4 bar/50 psi 80 mm Ø, for plugging for 36.011 - 36.012 gauges
36.42	114541	Pressure gauge 0 to 12 bar/170 psi 80 mm Ø, for plugging for 36.013 - 36.014 gauges
36.43	114542	Pressure gauge 0 to 25 bar/350 psi 80 mm Ø, for plugging for 36.015 gauge



36.42