


## Datasheet for: 100584


**Service unit 3-part »multifix« with PC container, Size 3, G 3/4**

Service unit 3-part »multifix« with polycarbonate container, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	FRL 34 K-HA
Article number	100584
EAN/barcode	 4047322345460
Your price	168,65 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	200.8 mm
B	246.3 mm
Bowl	Polycarbonate container
C	99.0 mm
Condensate drain	Semi-automatic
D	147.3 mm
DN	25.0
Filter rating	5.0 $\mu\text{m}$
Flow rate	3000 l/min
Flow rate measurement	At $P_1 = 8 \text{ bar}$ , $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK093
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar

Sealant	NBR
Series	multifix
Sight dome	PA
Size	3
Spring bonnet	POM-brass
Thread	G 3/4

## Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100584	G 3/4	Die-cast zinc	5.0 $\mu\text{m}$	3000 l/min	3	25.0	168,65 € / Stk
100581	G 1/4	Die-cast zinc	5.0 $\mu\text{m}$	1100 l/min	1	6.0	114,90 € / Stk
100585	G 1	Aluminium	40.0 $\mu\text{m}$	11300 l/min	5	25.0	471,23 € / Stk
100582	G 3/8	Die-cast zinc	5.0 $\mu\text{m}$	1100 l/min	1	10.0	114,90 € / Stk
100583	G 1/2	Die-cast zinc	5.0 $\mu\text{m}$	3000 l/min	3	15.0	168,65 € / Stk

## More Pictures

