


Datasheet for: 156635


Filling unit »FUTURA«, pneumatically actuated, Size 2, G 1/2

Filling unit »FUTURA«, pneumatically actuated, Size 2, G 1/2, Exhaust G 1/2, Input pressure 2.5 - 16 bar, Temp. -10 °C to 50 °C . The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure. The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve). It is connected and disconnected by means of the 3/2-way valve. The filling time can be altered by turning the adjusting screw.

Type number	FU 958-137
Article number	156635
EAN/barcode	 4047322628266
Your price	168,77 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	126.0 mm
B	117.6 mm
C	61.1 mm
Connecting thread	Material: Die-cast zinc
D	56.5 mm
Exhaust air	G 1/2
Flow rate	3400 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop $\Delta_p = 1$ bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.5 bar
Min. temperature range	-10 °C
Page No.	HK061
Series	FUTURA
Size	2
Thread	G 1/2

Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
156635	G 1/2	G 1/2	3400 l/min	2	168,77 € / Stk
156636	G 3/4	G 1/2	9000 l/min	4	357,64 € / Stk
156637	G 1	G 1/2	9000 l/min	4	357,64 € / Stk
156632	G 1/4	G 1/4	1400 l/min	1	138,65 € / Stk
156634	G 3/8	G 1/2	3400 l/min	2	168,77 € / Stk
156633	G 3/8	G 1/4	1400 l/min	1	138,65 € / Stk

More Pictures

