

Datasheet for: 103857


Check valve, Lightweight construction, Stainless steel, G 2 1/2

Check valve, Lightweight construction, Stainless steel 1.4301, Operating temperature -20 °C to 150 °C, G 2 1/2, PN max. 16 bar . Stainless steel check valve with full bore and very low opening pressure, no maintenance required. Applications: Compressed air, water, neutral gases, gaseous and liquid non-corrosive media, oils.

Type number	228.212-ES
-------------	------------

Article number	103857
----------------	--------

EAN/barcode	 4047322382540
-------------	--



Your price	279,21 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	80.0 mm
C	113.0 mm
Housing	Stainless steel 1.4301
L	141.5 mm
Max. operating pressure	16 bar
Max. operating temperature	150 °C
Min. opening pressure	0.03 bar
Min. operating temperature	-20 °C
Page No.	WEB
Sealant	FKM
Spring	Stainless steel 1.4301
Thread	G 2 1/2

Variants

Article number	Thread	Price
103857	G 2 1/2	279,21 € / Stk
103850	G 3/8	30,29 € / Stk
103852	G 3/4	41,29 € / Stk
103851	G 1/2	31,03 € / Stk
103853	G 1	46,78 € / Stk
103854	G 1 1/4	65,22 € / Stk
103855	G 1 1/2	76,29 € / Stk
103858	G 3	391,98 € / Stk
103856	G 2	150,12 € / Stk
103849	G 1/4	30,29 € / Stk

More Pictures

