

Datasheet for: 106953


Throttle check valve, Discharge throttle (»C«) quick connector

Throttle check valve, Discharge throttle (»C«) quick connector Hose 6/4, G 1/4, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	333.014-6
Article number	106953
EAN/barcode	 4047322180337
Your price	12,93 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	51.4 mm
C	26.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	6 / 4 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK501
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/4
a/f	17 mm

Variants

Article number	Thread	For hose	a/f	Price
106953	G 1/4	6 / 4 mm	17 mm	12,93 € / Stk
106948	M5	4 / 2.5 mm	8 mm	11,76 € / Stk
106949	M5	5 / 3 mm	8 mm	11,76 € / Stk
106950	M5	6 / 4 mm	8 mm	11,76 € / Stk
106951	G 1/8	6 / 4 mm	14 mm	11,23 € / Stk
106952	G 1/8	8 / 6 mm	14 mm	11,23 € / Stk
106954	G 1/4	8 / 6 mm	17 mm	12,93 € / Stk
106955	G 1/4	10 / 8 mm	17 mm	13,16 € / Stk

More Pictures

