


Datasheet for: 107229



Quick-connect coupl. I.D. 7.2, bright brass, Sleeve I.D. 6, M12x1

Quick-connect coupling I.D. 7.2, bright brass, Sleeve I.D. 6, Bulkhead thread M12x1, Operating pre. 0-35 bar, Temp. -20°C to 100°C. Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Type number	243.340
Article number	107229
EAN/barcode	 4047322285360
Your price	13,55 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Bulkhead fitting	M12x1
Connection	I.D. 6
DN	7.2
Flow rate	1000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	60.0 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)

Page No.	HK533
Page No. SK	SK016
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve body	Brass with a bare metal surface
a/f	21 mm

Variants

Article number	Bulkhead fitting	Connection	Length	Price
107229	M12x1	I.D. 6	60.0 mm	13,55 € / Stk
107231	G 1/4	I.D. 10	72.0 mm	14,71 € / Stk
107230	M12x1	I.D. 8	63.0 mm	14,61 € / Stk

More Pictures

