

Datasheet for: 136575


Bushing with exterior hexagonal, reduced G 3/4 i., M14x1.5 i.

Bushing, exterior hexagonal, red. G 3/4 i. M14x1.5 i. nickel-plated brass, Max. working pressure 25 bar, Max. operating temp. 150°C . Suitable for air, water, oil, steam, etc.

Type number	MSN252MU34M14
Article number	136575
EAN/barcode	 4047322506700
Your price	10,12 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

L1	28.0 mm
Material	Nickel-plated brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	HK779
Thread 1	G 3/4
Thread 2	M14x1.5
a/f	32 mm

Variants

Article number	Thread 1	Thread 2	a/f	Price
136575	G 3/4	M14x1.5	32 mm	10,12 € / Stk
136570	G 1/8	G 1/4	17 mm	2,12 € / Stk
136576	G 3/4	M16x1.5	32 mm	10,12 € / Stk
136573	G 1/2	M14x1.5	27 mm	7,11 € / Stk

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>a/f</i>	<i>Price</i>
136571	G 1/4	G 3/8	22 mm	3,18 € / Stk
136574	G 1/2	M16x1.5	27 mm	7,55 € / Stk
136572	G 3/8	G 1/2	27 mm	3,88 € / Stk