


## Datasheet for: 107357



### Quick-connect coupling I.D. 7.6, gal. steel/brass, R 3/8 ET

Quick-connect coupling I.D. 7.6, galvanised steel / brass, R 3/8 ET, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C . High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The stream line type has an integrated hose stem.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | 244.62                                                                                             |
| Article number | 107357                                                                                             |
| EAN/barcode    | <br>4047322060950 |
| Your price     | 16,18 € / Stk                                                                                      |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                          |                                   |
|--------------------------|-----------------------------------|
| Connection               | R 3/8 ET                          |
| DN                       | 7.6                               |
| Flow rate                | 2100 l/min (air)                  |
| Flow rate measurement    | at 6 bar and $\Delta p = 0.5$ bar |
| Housing                  | Steel                             |
| Length                   | 61.0 mm                           |
| Max. ambient temperature | 100 °C                            |
| Max. medium temperature  | 100 °C                            |
| Max. operating pressure  | 16 bar                            |
| Min. ambient temperature | -20 °C                            |
| Min. medium temperature  | -20 °C                            |
| Page No.                 | WEB                               |
| Sealant                  | NBR                               |
| Sleeve                   | Hardened and nickel-plated steel  |
| Spring                   | Stainless steel                   |
| a/f                      | 20 mm                             |

## Variants

| Article number | Connection | Length  | a/f   | Price         |
|----------------|------------|---------|-------|---------------|
| 107357         | R 3/8 ET   | 61.0 mm | 20 mm | 16,18 € / Stk |
| 107356         | R 1/4 ET   | 63.0 mm | 20 mm | 16,18 € / Stk |
| 107358         | R 1/2 ET   | 56.0 mm | 22 mm | 16,50 € / Stk |

## More Pictures

