


Datasheet for: 107358



Quick-connect coupling I.D. 7.6, gal. steel/brass, R 1/2 ET

Quick-connect coupling I.D. 7.6, galvanised steel / brass, R 1/2 ET, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C. High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The stream line type has an integrated hose stem.

Type number	244.63
Article number	107358
EAN/barcode	 4047322060967
Your price	16,50 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	R 1/2 ET
DN	7.6
Flow rate	2100 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Steel
Length	56.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	16 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	WEB
Sealant	NBR
Sleeve	Hardened and nickel-plated steel
Spring	Stainless steel
a/f	22 mm

Variants

Article number	Connection	Length	a/f	Price
107358	R 1/2 ET	56.0 mm	22 mm	16,50 € / Stk
107356	R 1/4 ET	63.0 mm	20 mm	16,18 € / Stk
107357	R 3/8 ET	61.0 mm	20 mm	16,18 € / Stk

More Pictures

