

## Datasheet for: 107361


**Quick-connect coupling I.D. 7.6, gal. steel/brass, G 1/2 IT**

Quick-connect coupling I.D. 7.6, galvanised steel / brass, G 1/2 IT, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C . High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The stream line type has an integrated hose stem.

Type number	244.73
Article number	107361
EAN/barcode	 4047322060998
Your price	16,18 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/2 IT
DN	7.6
Flow rate	2100 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Steel
Length	60.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	16 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	WEB
Sealant	NBR
Sleeve	Hardened and nickel-plated steel
Spring	Stainless steel
a/f	25 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>a/f</i>	<i>Price</i>
107361	G 1/2 IT	60.0 mm	25 mm	16,18 € / Stk
107359	G 1/4 IT	57.0 mm	20 mm	16,18 € / Stk
107360	G 3/8 IT	60.0 mm	22 mm	16,18 € / Stk

## More Pictures

