


Datasheet for: 107365


Quick-connect coupling I.D. 7.6, gal. steel/brass, Sleeve I.D. 10

Quick-connect coupling I.D. 7.6, galvanised steel / brass, Sleeve I.D. 10, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C . High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The stream line type has an integrated hose stem.

Type number	244.83
Article number	107365
EAN/barcode	 4047322061025
Your price	16,18 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 10
DN	7.6
Flow rate	2100 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Steel
Length	70.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	16 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	WEB
Sealant	NBR
Sleeve	Hardened and nickel-plated steel
Spring	Stainless steel

Variants

Article number	Connection	Length	Price
107365	I.D. 10	70.0 mm	16,18 € / Stk
107362	I.D. 6	67.0 mm	16,50 € / Stk
107363	I.D. 8	70.0 mm	16,18 € / Stk
107366	I.D. 13	68.0 mm	16,18 € / Stk
107364	I.D. 9	70.0 mm	16,18 € / Stk

More Pictures

