


Datasheet for: 107396


Compressed air distributor »Multi-Link«, 4 standard couplings 7.6

Compressed air distributor »Multi-Link«, with standard coupling I.D. 7.6, Removal unit 4, Operating pressure max. 16 bar . Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 2 to 5 bleed units, optionally with: - G 1/2 female threaded connection for individually adaption output segments - DN 7.6 quick disconnect safety couplings

Type number	VTM-4K
Article number	107396
EAN/barcode	 4047322350334
Your price	171,56 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Bleed units	4
Connecting thread	G 1/2 female
Connection	Standard couplings DN 7.6
Material	Galvanised steel / brass
Max. operating pressure	16 bar
Max. temperature range	100 °C
Medium	Compressed air, non-corrosive gases
Min. temperature range	-20 °C
Page No.	WEB
Page No. SF	SF075
Sealant	NBR

Variants

<i>Article number</i>	<i>Bleed units</i>	<i>Price</i>
107396	4	171,56 € / Stk
107395	3	128,88 € / Stk
107397	5	209,91 € / Stk
107393	1	84,72 € / Stk
107394	2	103,01 € / Stk