


Datasheet for: 137015


Push-in T-fitting »metallica« rotating, R 1/2 o., hose ext. Ø 14

Push-in T-fitting »metallica«, rotating, R 1/2 o., for hose exterior Ø 14 mm, Working pressure max. 16 bar, nickel-plated brass . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	8855.012-14
Article number	137015
EAN/barcode	 4047322509992
Your price	15,19 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	14 mm
L1	64.0 mm
L2	35.5 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK714
Series	metallica
Sleeve	Nickel-plated brass
Thread	R 1/2
a/f	22 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
137015	R 1/2	14 mm	22 mm	15,19 € / Stk
108930	R 1/8	4 mm	13 mm	6,03 € / Stk
108935	R 1/4	10 mm	16 mm	8,31 € / Stk
108934	R 1/4	8 mm	14 mm	6,26 € / Stk
108936	R 3/8	8 mm	18 mm	7,36 € / Stk
108932	R 1/8	8 mm	13 mm	6,03 € / Stk
108933	R 1/4	6 mm	14 mm	6,03 € / Stk
108931	R 1/8	6 mm	13 mm	5,69 € / Stk
108937	R 3/8	10 mm	18 mm	10,35 € / Stk
108938	R 3/8	12 mm	20 mm	11,38 € / Stk
108939	R 1/2	12 mm	22 mm	12,94 € / Stk
137014	R 3/8	14 mm	22 mm	14,12 € / Stk

More Pictures

