


Datasheet for: 107605



Safety coupling I.D. 7.8, Bi-Tec type, nickel-pl. brass, R 3/8 ET

Safety coupling I.D. 7.8, Bi-Tec type, nickel-plated brass, R 3/8 ET, Operating pressure max. 20 bar, Temp. -20 °C to 100 °C . Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Type number	249.05
Article number	107605
EAN/barcode	 4047322062435
Your price	25,55 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	R 3/8 ET
DN	7.8
Flow rate	1400 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Nickel-plated brass
Length	81.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	20 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	WEB
Page No. SF	SF072
Sealant	NBR
Sleeve	Anodised aluminium
Spring	Stainless steel

Unlocking sleeve
 Valve body
 a/f

Hardened, nickel-plated steel
 Nickel-plated brass
 19 mm

Variants

Article number	Connection	Length	a/f	Price
107605	R 3/8 ET	81.0 mm	19 mm	25,55 € / Stk
107604	R 1/4 ET	80.0 mm	19 mm	25,11 € / Stk
107606	R 1/2 ET	87.0 mm	22 mm	25,89 € / Stk

More Pictures

