


Datasheet for: 137330


Stainless steel casting pressure regulator, G 3/4, 1.7 - 17.5 bar

Stainless steel casting pressure regulator, 1.4401, secondary venting (reversible), Size 3, G 3/4, Control range 1.7 - 17.5 bar . Stainless steel regulators for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc. Pressure setting by T-handle.

Type number	580RC3-34-17
Article number	137330
EAN/barcode	 4047322513135
Your price	449,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	82.0 mm
B	170.0 mm
C	49.0 mm
D	121.0 mm
Diaphragms	NBR/PTFE
Flow rate	9260 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p \leq 1$ bar
Housing	Stainless steel casting 1.4401 (AISI 316)
Max. ambient temperature	80 °C
Max. control range	17.5 bar
Max. input pressure	30 bar
Max. medium temperature	80 °C
Min. control range	1.7 bar
Page No.	HK148
Sealant	NBR
Size	3
Thread	G 3/4

Variants

Article number	Thread	Min. control range	Max. control range	Flow rate	Size	Price
137330	G 3/4	1.7 bar	17.5 bar	9260 l/min	3	449,34 € / Stk
137333	G 1 1/2	0.4 bar	4.0 bar	11270 l/min	4	1.159,08 € / Stk
137328	G 1/2	1.7 bar	17.5 bar	8070 l/min	3	449,34 € / Stk
137332	G 1	1.7 bar	17.5 bar	10790 l/min	4	1.159,08 € / Stk
137331	G 1	0.4 bar	4.0 bar	10790 l/min	4	1.159,08 € / Stk
137325	G 3/8	0.4 bar	4.0 bar	3965 l/min	1	363,63 € / Stk
137334	G 1 1/2	1.7 bar	17.5 bar	11270 l/min	4	1.159,08 € / Stk
137323	G 1/4	0.4 bar	4.0 bar	2125 l/min	1	363,63 € / Stk
137327	G 1/2	0.4 bar	4.0 bar	8070 l/min	3	449,34 € / Stk
137326	G 3/8	1.7 bar	17.5 bar	3965 l/min	1	363,63 € / Stk
137324	G 1/4	1.7 bar	17.5 bar	2125 l/min	1	363,63 € / Stk
137329	G 3/4	0.4 bar	4.0 bar	9260 l/min	3	449,34 € / Stk

More Pictures

