

Datasheet for: 107830


GEKA threaded piece, rigid, Stainless steel, G 1/2 exterior

GEKA threaded piece, rigid, Stainless steel, G 1/2 exterior, Operating pressure max. 40 bar, Medium/ambient temp. -10 °C to 150 °C . Claw couplings (claw distance: 40 mm) made of stainless steel (similar to 1.4581). Suitable for a wide range of applications, e.g. in the chemical, food processing, water management, vehicle construction, shipbuilding and aerospace industries, agriculture, environmental engineering, etc. The stainless steel series can be easily coupled to the standard brass series!

Type number	K 110 A-ES
Article number	107830
EAN/barcode	 4047322132923
Your price	24,59 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/2 ET
Max. ambient temperature	150 °C
Max. medium temperature	150 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK610
Sealant	FKM

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107830	G 1/2 ET	24,59 € / Stk
107831	G 3/4 ET	25,17 € / Stk
107832	G 1 ET	25,52 € / Stk
107833	G 1 1/4 ET	29,21 € / Stk