


Datasheet for: 137353


Blocking valve pneumat. actuated, single-acting NO, NBR, Rp 3/8

Blocking valve pneumat. actuated, single-acting, NO, nickel-plated brass, Temp. -20°C to 80°C, Control pressure 4.2-8 bar, Rp 3/8 . 2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. These valves have a full bore and - owing to the optimised design - only minimal flow losses. They are controlled by means of filtered compressed air.

Type number	351.971
Article number	137353
EAN/barcode	 4047322513364
Your price	98,08 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	NAMUR interface, direct: 2 x G 1/8
DN	10.0
H	46.0 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
L	98.0 mm
Max. operating pressure	10 bar
Max. operating temperature	80 °C
Max. pilot pressure	8.0 bar
Min. operating temperature	-20 °C
Min. pilot pressure	4.2 bar
Mounting position	Any
Page No.	HK345
Sealant	NBR
Spring	Stainless steel
Thread	Rp 3/8
Version	single-acting - spring to open

Variants

Article number	Thread	DN	Price
137353	Rp 3/8	10.0	98,08 € / Stk
137354	Rp 1/2	15.0	110,33 € / Stk
137356	Rp 1	25.0	146,34 € / Stk
137358	Rp 1 1/2	40.0	273,23 € / Stk
137357	Rp 1 1/4	32.0	219,09 € / Stk
137359	Rp 2	50.0	378,11 € / Stk
137355	Rp 3/4	20.0	131,03 € / Stk

More Pictures

