

Datasheet for: 108156


Kamlok cap plug, DP type, St. steel 1.4401, Size 1, Plug Ø 37

Kamlok cap plug, DP type, Stainless steel 1.4401, Size 1, Plug Ø 37 mm, Operating pressure max. 16 bar, Temp. -20 °C to 95 °C . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1119.10-ES
-------------	------------

Article number	108156
----------------	--------

EAN/barcode	 4047322404976
-------------	--



Your price	6,33 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	36.6 mm
C	42.0 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK624
Plug Ø	37 mm
Sealant	NBR, resistant to oils and benzine
Size	1

Variants

Article number	Size	Plug Ø	Price
108156	1	37 mm	6,33 € / Stk
108159	2	63 mm	18,62 € / Stk
108155	3/4	32 mm	4,95 € / Stk
108158	1 1/2	53 mm	12,61 € / Stk
108160	2 1/2	76 mm	25,38 € / Stk
108157	1 1/4	46 mm	8,65 € / Stk
108161	3	92 mm	34,83 € / Stk
108162	4	120 mm	48,81 € / Stk

More Pictures

