

Brass with a bare metal surface



Tees

Brass with a bare metal surface MS 58




Type No. 254.xx


Art. No. 112714 to 112737

Max. 150 °C

 Parallel thread
acc. to DIN EN ISO 228-1
Conical thread
acc. to DIN 2999

Type No.	Art. No.	Thread	Dimensions						
			Ø	Op. press. (bar)	H	L ₁	L ₂	a/f	
		m / m / m							
254.02	112714	R 1/8	6.0	60	8.0	37.0	18.5	10	
254.03	112715	R 1/4	8.0	60	11.0	47.0	23.5	13	
254.04	112716	R 3/8	11.0	60	12.5	52.0	26.0	17	
254.05	112717	R 1/2	15.0	60	14.0	62.0	31.0	21	
254.06	112718	R 3/4	19.0	60	16.0	66.4	33.0	25	
254.07	112719	R 1	24.0	60	17.0	78.0	39.0	30	
		f / f / f							
254.33	112720	G 1/8	6.0	60	8.0	42.0	21.0	10	
254.34	112721	G 1/4	8.0	60	11.0	51.0	25.5	13	
254.35	112722	G 3/8	11.0	60	11.5	56.0	28.0	17	
254.39	112723	G 1/2	15.0	60	15.0	67.0	33.5	21	
254.48	112724	G 3/4	19.0	60	16.5	73.0	36.5	25	
254.49	112725	G 1	24.0	60	19.0	90.0	45.0	30	
		f / m / f							
				Op. press. (bar)	H1	H2	L ₁	L ₂	a/f
254.41	112726	G/R 1/8	6.0	60	8.0	8.0	42.0	18.5	10
254.42	112727	G/R 1/4	8.0	60	11.0	11.0	51.0	23.5	13
254.43	112728	G/R 3/8	11.0	60	11.5	11.5	56.0	26.0	17
254.44	112729	G/R 1/2	15.0	60	14.0	14.0	67.0	31.0	21
254.45	112730	G/R 3/4	19.0	60	16.0	16.5	73.0	33.0	25
254.46	112731	G/R 1	24.0	60	17.5	19.0	90.0	39.0	30



Type No.	Art. No.	Thread	Dimensions							
			Ø	Op. press. (bar)	H1	H2	L ₁	L ₂	af	
		f / f / m								
254.71	112732	G/R 1/8	6.0	60	8.0	6.0	39.5	21.0	10	
254.72	112733	G/R 1/4	8.0	60	10.0	11.5	49.0	25.5	13	
254.73	112734	G/R 3/8	11.0	60	11.5	11.5	54.0	28.0	17	
254.74	112735	G/R 1/2	15.0	60	14.5	14.0	64.5	33.0	21	
254.75	112736	G/R 3/4	19.0	60	16.0	15.5	69.5	36.0	25	
254.76	112737	G/R 1	24.0	60	17.5	16.5	84.0	45.0	30	

Nickel-plated brass



Tees

Nickel-plated brass
MS 58

Type No. N 254.xx

Art. No. 112759 to 112797

Max. 150 °C

Parallel thread
acc. to DIN EN ISO 228-1
Conical thread
acc. to DIN 2999

Type No.	Art. No.	Thread	Dimensions						
			Ø	Op. press. (bar)	H	L ₁	L ₂	a/f	
m / m / m									
N 254.02	112759	R 1/8	6.0	60	8.0	37.0	18.5	10	
N 254.03	112760	R 1/4	8.0	60	11.0	47.0	23.5	13	
N 254.04	112761	R 3/8	11.0	60	11.5	52.0	26.0	17	
N 254.05	112762	R 1/2	15.0	60	14.0	62.0	31.0	21	
N 254.06	112763	R 3/4	19.0	60	16.2	66.4	33.0	25	
N 254.07	112764	R 1	24.0	60	16.1	78.0	39.0	30	
f / f / f									
N 254.32	112765	M5	-	60	5.0	11.0	22.0	9	
N 254.33	112766	G 1/8	6.0	60	12.3	21.0	42.0	10	
N 254.34	112767	G 1/4	8.0	60	14.0	25.5	51.0	13	
N 254.35	112768	G 3/8	11.0	60	14.0	28.0	56.0	17	
N 254.39	112769	G 1/2	15.0	60	16.0	33.5	67.0	21	
N 254.48	112770	G 3/4	19.0	60	17.5	36.5	73.0	25	
N 254.49	112771	G 1	24.0	60	21.0	45.0	90.0	30	
f / m / f									
N 254.40	112772	M5	2.0	60	4.0	22.0	11.5	9	
N 254.41	112773	G/R 1/8	6.0	60	9.0	42.0	18.5	10	
N 254.42	112774	G/R 1/4	8.0	60	13.0	51.0	23.5	13	
N 254.43	112775	G/R 3/8	11.0	60	13.0	56.0	26.0	17	
N 254.44	112776	G/R 1/2	15.0	60	15.0	67.0	31.0	21	
N 254.45	112777	G/R 3/4	19.0	60	17.0	73.0	33.0	25	
N 254.46	112778	G/R 1	24.0	60	17.0	90.0	39.0	30	

Type No.	Art. No.	Thread	Dimensions						
			Ø	Op. press. (bar)	H	L ₁	L ₂	a/f	
		f / f / m							
N 254.70	112779	M5		60	4.0	22.5	11.0	9	
N 254.71	112780	G/R 1/8	6.0	60	11.0	39.5	21.0	10	
N 254.72	112781	G/R 1/4	8.0	60	13.0	49.0	23.5	13	
N 254.73	112782	G/R 3/8	11.0	60	13.5	54.0	28.0	17	
N 254.74	112783	G/R 1/2	15.0	60	15.0	64.5	33.5	21	
N 254.75	112784	G/R 3/4	19.0	60	16.5	69.5	36.5	25	
N 254.76	112785	G/R 1	24.0	60	17.5	84.0	45.0	30	
		m / f / m							
N 254.81	112786	G/R 1/8	-	60	8.0	37.0	21.0	10	
N 254.82	112787	G/R 1/4	-	60	11.0	47.0	25.5	13	
N 254.83	112788	G/R 3/8	11.0	60	11.5	52.0	28.0	17	
N 254.84	112789	G/R 1/2	15.0	60	15.0	62.0	33.5	21	
N 254.85	112790	G/R 3/4	19.0	60	16.0/16.5	66.5	36.5	25	
N 254.86	112791	G/R 1	24.0	60	17.5/18.0	78.0	45.0	30	
		m / m / f							
N 254.91	112792	G/R 1/8	6.0	60	8.0/8.5	39.5	18,5	10	
N 254.92	112793	G/R 1/4	8.0	60	11.5/11.0	49.0	23,5	13	
N 254.93	112794	G/R 3/8	11.0	60	11.5	54.0	26,0	17	
N 254.94	112795	G/R 1/2	15.0	60	15.0	64.5	31,0	21	
N 254.95	112796	G/R 3/4	19.0	60	16.0/16.5	69.5	33,0	25	
N 254.96	112797	G/R 1	23.8	60	17.5/19.0	84.0	39,0	30	