

Datasheet for: 108545

**Pivoting suction pad attachment »flexolink« G 1/4 IT, M10x1.25 ET**

Pivoting suction pad attachment »flexolink«, G 1/4 IT, M10x1.25 ET, Steel / rubber, Bracket 12°, Bending moment 8 N. Flexible suction pad mounting By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces. Advantages:

- Very good adaptation to sloping workpiece surfaces

- Automatically resets into the initial position

- Vacuum-tight design with integrated protection against damage


Applications:

- Handling workpieces with sloping surfaces using large-area suction pads

- Handling large sheets of materials that may sag when lifted

- Can be used together with spring plungers to compensate for differing workpiece heights and uneven surfaces



Type number	FLK 1410
Article number	108545
EAN/barcode	 4047322200646
Your price	33,30 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Angle	12 °
Bending moment	8 N
H	27.0 mm
L1	10.5 mm
L2	8.0 mm
Material	Steel, rubber
Page No.	WEB
Thread 1	G 1/4 IT
Thread 2	M10x1.25 ET
Vertical load	500 N
Weight	26.0 g
a/f	17 mm

## Variants

Article number	Thread 2	Vertical load	Bending moment	Price
108545	M10x1.25 ET	500 N	8 N	33,30 € / Stk
108546	G 1/4 ET	750 N	10 N	31,81 € / Stk

## More Pictures

