

Datasheet for: 141016


Strainer nickel-plated brass, G 2, DN 50, mesh width 0.05 mm

Dirt strainer, nickel-plated brass, Sieve insert mesh width 0.05 mm, Operating temp. -20 °C to 110 °C, G 2, DN 50, PN max. 20 bar . Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

Type number	60-8 N-0,05
-------------	-------------

Article number	141016
----------------	--------

EAN/barcode	 4047322547420
-------------	----------------------------------------------------------------------------------------------------

Your price	63,43 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

C	88.5 mm
DN	50.0
Head piece	Nickel-plated brass
Housing	Nickel-plated brass
L	126.0 mm
Max. operating pressure	20 bar
Max. operating temperature	110 °C
Mesh size	0.05 mm
Min. operating temperature	-20 °C
Page No.	HK370
Screen	Stainless steel
Sealant	NBR O-ring
Standard thread	G thread acc. to ISO 228-1, tolerance class B
Thread	G 2
a/f 1	67.0 mm
a/f 2	46.0 mm

Variants

Article number	Thread	DN	a/f 1	a/f 2	Price
141016	G 2	50.0	67.0 mm	46.0 mm	63,43 € / Stk
141012	G 3/4	20.0	31.0 mm	27.0 mm	13,70 € / Stk
141010	G 3/8	10.0	21.0 mm	20.0 mm	8,50 € / Stk
141009	G 1/4	8.0	18.0 mm	20.0 mm	8,50 € / Stk
141015	G 1 1/2	40.0	54.0 mm	38.0 mm	38,70 € / Stk
141013	G 1	25.0	38.0 mm	32.0 mm	20,38 € / Stk
141014	G 1 1/4	32.0	47.0 mm	36.0 mm	29,85 € / Stk
141011	G 1/2	15.0	25.0 mm	20.0 mm	8,92 € / Stk

More Pictures

