

Datasheet for: 141567


Quick-connect coupling I.D. 19, Bright brass, Sleeve I.D. 16

Quick-connect coupling I.D. 19, Bright brass, Sleeve I.D. 16, Operating pressure - 35 bar, Med. / ambient temp. -20 °C to 100 °C . Single-sided blocking and quick connect coupling with extremely high flow performance. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Machine and plant engineering, manufacturing industry, workshops.

Type number	419.26
Article number	141567
EAN/barcode	 4047322568395
Your price	179,90 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 16
DN	19
Flow rate	8700 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	114.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK555
Page No. SK	SK037
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Threaded piece	Brass with a bare metal surface

Valve
a/f

Brass with a bare metal surface
41 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
141567	I.D. 16	179,90 € / Stk
141568	I.D. 19	179,90 € / Stk
141569	I.D. 25	191,89 € / Stk

More Pictures

