


Datasheet for: 133541


Stainless steel filter regulator, 1.4401, G 3/8, 0.4 - 4.0 bar

Stainless steel filter regulator, 1.4401, with secondary venting (reversible), Size 1, G 3/8, Control range 0.4 - 4.0 bar . Stainless steel filter regulators with self-relieving (not for liquid media) for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc. Pressure setting by hexagon head screw.

Type number	580FRM1-38-4
Article number	133541
EAN/barcode	 4047322479493
Your price	507,35 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	64.0 mm
B	271.0 mm
C	117.0 mm
Condensate drain	Manual drain valve
Diaphragms	NBR/PTFE
Filter rating	25.0 μ m
Flow rate	3200 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar
Housing	Stainless steel 1.4401 (AISI 316)
Max. ambient temperature	60 °C
Max. control range	4.0 bar
Max. input pressure	30 bar
Max. medium temperature	80 °C
Min. control range	0.4 bar
Page No.	HK150
Sealant	NBR
Size	1
Thread	G 3/8

Variants

Article number	Thread	Min. control range	Max. control range	Flow rate	Size	Price
133541	G 3/8	0.4 bar	4.0 bar	3200 l/min	1	507,35 € / Stk
133539	G 1/4	0.4 bar	4.0 bar	2495 l/min	1	507,35 € / Stk
133546	G 3/4	1.7 bar	17.5 bar	9630 l/min	3	618,75 € / Stk
133548	G 1	1.7 bar	17.5 bar	10000 l/min	4	2.245,80 € / Stk
133545	G 3/4	0.4 bar	4.0 bar	9630 l/min	3	618,75 € / Stk
133542	G 3/8	1.7 bar	17.5 bar	3200 l/min	1	507,35 € / Stk
133540	G 1/4	1.7 bar	17.5 bar	2495 l/min	1	507,35 € / Stk
133547	G 1	0.4 bar	4.0 bar	10000 l/min	4	2.245,80 € / Stk
133543	G 1/2	0.4 bar	4.0 bar	5440 l/min	3	618,75 € / Stk
133544	G 1/2	1.7 bar	17.5 bar	5440 l/min	3	618,75 € / Stk

More Pictures

