

Datasheet for: 115617



Quick-connect coupling I.D. 7.2 »connect line«, G 1/2 ET

Quick-connect coupling I.D. 7.2 »connect line«, nickel-plated brass, G 1/2 ET, Operating pressure - 35 bar, Temp. -20°C to 100°C . Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Type number	243.03-N E
Article number	115617
EAN/barcode	 4047322057615
Your price	4,87 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/2 ET
DN	7.2
Flow rate	1000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Nickel-plated brass
Length	40.5 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK538

Page No. AS	AS098
Page No. SK	SK024
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Nickel-plated brass
Spring	Stainless steel
Valve body	Nickel-plated brass
a/f	21 mm

Variants

Article number	Connection	Length	Price
115617	G 1/2 ET	40.5 mm	4,87 € / Stk
115613	G 1/4 ET	39.0 mm	4,87 € / Stk
115615	G 3/8 ET	39.0 mm	4,87 € / Stk

More Pictures

