

Datasheet for: 110368


Straight push-in fitting, G 1/2 o., for hose exterior Ø 12 mm

Straight push-in fitting, Exterior hexagonal, G 1/2 o., for hose exterior Ø 12 mm, Working pressure max. 15 bar, Stainless steel . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	44.012-12 ES
Article number	110368
EAN/barcode	 4047322270144
Your price	44,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	12 mm
L1	26.4 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/2
Working pressure pulsate a/f	10.0 bar 22 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>a/f</i>	<i>Price</i>
110368	G 1/2	12 mm	22 mm	44,81 € / Stk
110365	G 1/4	10 mm	16 mm	26,45 € / Stk
110367	G 3/8	12 mm	21 mm	41,40 € / Stk
110364	G 1/4	8 mm	16 mm	25,45 € / Stk
110363	G 1/4	6 mm	16 mm	22,51 € / Stk
110361	G 1/8	6 mm	13 mm	20,09 € / Stk
110366	G 3/8	10 mm	17 mm	32,18 € / Stk
110360	G 1/8	4 mm	13 mm	18,44 € / Stk
110362	G 1/8	8 mm	14 mm	23,49 € / Stk
110359	M5	4 mm	9 mm	18,41 € / Stk

More Pictures

