

Datasheet for: 110379


Push-in L-fitting, rotating, M5 o., for hose exterior Ø 4 mm

Push-in L-fitting, rotating, M5 o., for hose exterior Ø 4 mm, Working pressure max. 15 bar, Stainless steel 1.4404. For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	43.005-4 ES
-------------	-------------

Article number	110379
----------------	--------

EAN/barcode



4047322387286

Your price	34,84 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	4 mm
L1	17.0 mm
L2	14.8 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	DIN 13-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	M5
Working pressure pulsate	10.0 bar
a/f	9 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110379	M5	4 mm	9 mm	34,84 € / Stk
110381	G 1/8	6 mm	13 mm	39,31 € / Stk
110384	G 1/4	8 mm	16 mm	47,98 € / Stk
110388	G 1/2	12 mm	22 mm	88,50 € / Stk
110385	G 1/4	10 mm	16 mm	57,54 € / Stk
110380	G 1/8	4 mm	13 mm	38,54 € / Stk
110387	G 3/8	12 mm	21 mm	76,21 € / Stk
110386	G 3/8	10 mm	21 mm	63,25 € / Stk
110382	G 1/8	8 mm	13 mm	46,77 € / Stk
110383	G 1/4	6 mm	16 mm	46,44 € / Stk

More Pictures

