

Datasheet for: 110382


Push-in L-fitting, rotating, G 1/8 o., for hose exterior Ø 8 mm

Push-in L-fitting, rotating, G 1/8 o., for hose exterior Ø 8 mm, Working pressure max. 15 bar, Stainless steel 1.4404 . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	43.018-8 ES
-------------	-------------

Article number	110382
----------------	--------

EAN/barcode



4047322268806

Your price	46,77 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	8 mm
L1	22.0 mm
L2	18.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/8
Working pressure pulsate a/f	10.0 bar 13 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110382	G 1/8	8 mm	13 mm	46,77 € / Stk
110381	G 1/8	6 mm	13 mm	39,31 € / Stk
110384	G 1/4	8 mm	16 mm	47,98 € / Stk
110388	G 1/2	12 mm	22 mm	88,50 € / Stk
110385	G 1/4	10 mm	16 mm	57,54 € / Stk
110380	G 1/8	4 mm	13 mm	38,54 € / Stk
110387	G 3/8	12 mm	21 mm	76,21 € / Stk
110386	G 3/8	10 mm	21 mm	63,25 € / Stk
110383	G 1/4	6 mm	16 mm	46,44 € / Stk
110379	M5	4 mm	9 mm	34,84 € / Stk

More Pictures

