

Datasheet for: 110383


Push-in L-fitting, rotating, G 1/4 o., for hose exterior Ø 6 mm

Push-in L-fitting, rotating, G 1/4 o., for hose exterior Ø 6 mm, Working pressure max. 15 bar, Stainless steel 1.4404. For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	43.014-6 ES
-------------	-------------

Article number	110383
----------------	--------

EAN/barcode



4047322268813

Your price	46,44 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	6 mm
L1	21.5 mm
L2	20.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/4
Working pressure pulsate a/f	10.0 bar 16 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110383	G 1/4	6 mm	16 mm	46,44 € / Stk
110381	G 1/8	6 mm	13 mm	39,31 € / Stk
110384	G 1/4	8 mm	16 mm	47,98 € / Stk
110388	G 1/2	12 mm	22 mm	88,50 € / Stk
110385	G 1/4	10 mm	16 mm	57,54 € / Stk
110380	G 1/8	4 mm	13 mm	38,54 € / Stk
110387	G 3/8	12 mm	21 mm	76,21 € / Stk
110386	G 3/8	10 mm	21 mm	63,25 € / Stk
110382	G 1/8	8 mm	13 mm	46,77 € / Stk
110379	M5	4 mm	9 mm	34,84 € / Stk

More Pictures

