


Datasheet for: 116033



5/2-way valve manually »M5« Palm button, Emergency locking, G 1/4

5/2-way valve manually actuated »M5« Palm button, Emergency locking, bistable, G 1/4, Operating pre. 0-10 bar, Temp. -20°C to 70°C . 5/2-way valves - Manually operated, for panel mounting -

Type number	515.7104
Article number	116033
EAN/barcode	 4047322311748
Your price	56,11 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Exhaust connection	G 1/8
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Lever/switch colour	red
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Bistable
Page No.	HK457
Page No. AS	AS080
Symbol	2
Valve body	Aluminium alloy

Variants

Article number	Connection	Flow rate	Price
116033	G 1/4	550 l/min	56,11 € / Stk
116032	G 1/8	450 l/min	41,67 € / Stk

More Pictures

